

I Product Overview



Notes : Customization is available.

Thread	Metric (M), PG, NPT
Material	Stainless Steel 304/316 Claw : PA Sealing : NBR
Approvals	CE, RoHS, REACH
Protection Degree	IP68
Temperature	-40°C to 100°C, Short time to 120°C
Features	Extremely easy installation, simply insert cable through the assembled gland and tighten gland, lock nut until cable is secured. This cable glands are designed to withstand water, dust, salt, acid-base, alcohol, oil, and common solvent. Cable can be lock, other end can access devices on box body Also can choose thread according to the import and export for internal thread electric devices.

Thread Type	Product Model	Cable Range	Thread (O.D.) (C1)	Thread Length (C2)	Spanner Size	Qty / Bag
PG	TPE-PG7-SS	3-6.5	12.5	6.0	14.0	100
	TPE-PG9-SS	4-8	15.2	7.0	17.0	100
	TPE-PG11-SS	5-10	18.6	7.0	20.0	100
	TPE-PG13.5-SS	6-12	20.4	8.0	22.0	100
	TPE-PG16-SS	10-14	22.5	8.0	24.0	100
	TPE-PG21-SS	13-18	28.3	9.0	30.0	50
	TPE-PG29-SS	18-25	37.0	9.0	40.0	20
	TPE-PG36-SS	25-33	47.0	10.0	50.0	10
	TPE-PG42-SS	32-38	54.0	10.0	57.0	10
	TPE-PG48-SS	37-44	59.3	11.0	64.0	5
TPE-PG63-SS	42-52	70.8	15.0	78.0	5	

Thread Type	Product Model	Cable Range	Thread (O.D.) (C1)	Thread Length (C2)	Spanner Size	Qty / Bag
M	TPE-M8x1.0-SS	2-5	8.0	5.0	12.0	100
	TPE-M10x1.0-SS	3-6.5	10.0	6.5	14.0	100
	TPE-M12x1.5-SS	4-8	12.0	8.0	14.0	100
	TPE-M16x1.5-SS	5-10	16.0	8.0	17.0	100
	TPE-M20x1.5-SS	6-12	20.0	8.0	22.0	100
	TPE-M25x1.5-SS	13-18	25.0	9.0	30.0	50
	TPE-M32x1.5-SS	15-22	32.0	10.0	40.0	20
	TPE-M40x1.5-SS	22-30	40.0	11.0	50.0	20
	TPE-M50x1.5-SS	32-38	50.0	13.0	57.0	10
	TPE-M63x1.5-SS	37-44	63.0	14.0	64.0	5
	TPE-M72x2.0-SS	42-52	72.0	16.0	78.0	5
	TPE-M75x2.0-SS	42-52	75.0	16.0	80.0	5
	TPE-M80x2.0-SS	55-60	80.0	18.0	88.0	5
	TPE-M88x2.0-SS	65-70	88.0	18.0	94.0	5
	TPE-M100x2.0-SS	75-84	100.0	20.0	110.0	5

Thread Type	Product Model	Cable Range	Thread (O.D.) (C1)	Thread Length (C2)	Spanner Size	Qty / Bag
NPT	TPE-NPT3/8"-SS	4-8	17.0	8.0	18.0	100
	TPE-NPT1/2"-SS	6-12	21.2	8.0	22.0	100
	TPE-NPT3/4"-SS	13-18	26.5	9.0	30.0	50
	TPE-NPT1"-SS	18-25	33.2	11.0	40.0	20
	TPE-NPT1-1/4"-SS	25-33	41.9	13.0	50.0	10
	TPE-NPT1-1/2"-SS	32-38	48.0	14.0	57.0	10
	TPE-NPT2"-SS	37-44	60.0	14.0	65.0	5
	TPE-NPT2-1/2"-SS	42-52	72.6	15.0	77.0	5
TPE-NPT3"-SS	65-70	87.8	15.0	94.0	5	